







22' Bengal Boom Mower with 50" Rotary head and shown with optional Perimeter Guard.

DURABILITY INNOVATION

COMMITMENT







Ĩ=r⊃™



KOLOLA/



Cuts Up to 6" brush




Cuts Up to 5" brush



63" Flail with Grass knives



50" Flail with MBG knives





50" Flail with HDB knives

Independent Mower

Hydraulic System

Independent Mower Hydraulic System with Tandem Pump, Oil Cooler, In-Cab Temperature Gauge and Wheel Well Tank. Components shown are not the same on all tractor models. Independent Mower Hydraulic System not included on all models of tractors, check with your Tiger Dealer for your specific make and model of tractor.



TANDEM PUMP



OIL COOLER




IN-CAB TEMP GAUGE



HYDRAULIC WHEEL WELL TANK


<u>Ter Modular Erame</u>




To enhance the adaptability of our products, Tiger offers a modular mounting frame to ease mower change for your vegetation needs.

This unique design offers interchangeability with our boom and side mowers. With the Tiger modular frame, changing mower types can be accomplished in

approximately 8 hours. The boom mower frame should be installed at the onset to ensure the most effective framing system for future changes.









lectronic Boom

ositioning Se

- This optional feature can be added or retrofitted to any existing Tiger Boom Mower.
- Two sensors are located under the swivel of the boom arm.
- As the operator swings boom toward rear stow position, the sensors will identify the boom location (approx. 25" from stow position) and slow travel speed down and then stop directly above the rear stow.







501

BOOM ARM SWIVEL SLIDING OVER SENSORS

Video of Boom Positioning Sensor is located on Tiger website Look under Tiger Products and then Tiger Videos Options



Ì



PERIMETER GUARD





BOOM REST EXTENSION







"GROWLER" MULCHING HEAD Comes Standard with Hydraulic Head Tilt Stow Systems



<u>Li ep</u>™



3 PT OPEN STOW (30S) W/ DBL AXLE SUPPORT





BENGAL BRUTE STOW W/ SECONDARY BOOM BREAKAWAY



Î

50" ROTARY SWIVEL HEAD



60" ROTARY SWIVEL HEAD



Rotating Heads

50" ROTARY SWIVEL HEAD IN STOW POSITION

Transport width of pictured unit is 109" (JD 6105E, BB-22) Width depends on make and model of tractor **Options**



CABLE CONTROLS Hydraulically driven Cable Controls for Boom mower.



ELECTRONIC JOYSTICK Electronic over hydraulic Joystick Control.



PUMP/GRILL GUARD Additional protection with

Pump or Grill Guard.



AXLE STABILIZER or TIMBREN Additional stability and control for larger booms. Tractor specific, contact your Tiger Dealer for

the option that matches your model of tractor.



TRAVEL SAFETY LOCK Controlled from operator's

position.

Tiger Mowers LLC 3301 N Louise Ave. Sioux Falls, SD 57107 800-843-6849 www.tigermowers.com An Alamo Group Company

Contact Tiger Mowers LLC for tractor compatibility requirements. Specifications are subject to change without notice. Optional equipment may be shown. One Year Warranty on all products.



BRAKE VALVE Brake valve stops the cutter head in less than 7 seconds.

Dealer Info:



NITROGEN ACCUMULATOR Provides smooth response

and reduces shock.



SAFETY LIGHTING

Lightbar or rear signals on all boom mowers.



Awarded Contract

Contract # 070821-TGR

