



Ditch Bank Mower



- 130" Horizontal Reach
- Available in 540 or 1000 RPM
- 60" Cutting Width
- Slip Clutch Protection
- 2" Diameter Cut Capacity



DURABILITY INNOVATION

COMMITMENT

Tiger Features

Powerful. Versatile. Efficient.

When you need a mowing solution to take care of tree lines, ditches, and road right of ways with ease, look no further than the Tiger Ditch Bank Mower.

The mechanical drive system allows more power to be dispersed to the mower blades. This increases the speed of the mowing process and gives the operator the ability to cut debris up to 2" in diameter.

This mower features a unique infinity cast blade that is protected from additional wear and tear by the built in slip-clutch system.



Specifications

Cutting Width	60"
Cutting Height	1 1/2" to 12"
Hitch Requirements	CAT 2 std & CAT 3 std
Blade Measurements	1/2" x 4"
Minimum PTO HP Required	60 PTO HP
Minimum Tractor Weight	8,000 lbs.
Tractor PTO Speed	540 RPM or 1000 RPM
Horizontal Reach	130"
Average Height in Stow Position	18'
Cut Capacity	2" Diameter
Overload Protection	Slip Clutch
Range of Head Movement	40° Up / 40° Down
Skid Shoes	Replaceable
Weight	1900 lbs.

Dealer Info:

Tiger Corporation
3301 North Louise Ave.
Sioux Falls, SD, USA 57107
800.843.6849
www.tigermowers.com



An Alamo Group® Company
Specifications are subject to change. Optional equipment may be shown.

Meets All Applicable ANSI / SAE Test Standards.
© 2022 Tiger Corporation. All Rights Reserved. Printed in the USA.

