

TigerTM ROTARY AND FLAIL RailKut



Productivity. Performance. Power.

With the power and versatility of this innovative machine you can mow along rail, trim low branches or clear a highway intersection. Once job is done, you can drive the RailKut at highway speeds, improving overall productivity. Available in 22' and 24' boom lengths.



On/off rail
applications

DURABILITY INNOVATION

COMMITMENT



Features include right side viewing camera. Standard equipment on the RailKut.
Allows operator clear view of cutter head in operation while facing forward and steering vehicle.



Viewing Monitor located in cab of truck.

Tiger Specifications

Truck

F550 TRUCK

Four Wheel Drive Truck

Engine	Turbo 8 cyl. Diesel
Horsepower	325 HP @ 3,300 RPM
Fuel Tank	40 gallon, Supplies Both Engines
Steering	Dual Station, Power
Hyraul System	Bolt On Rated to 28,000 lbs. Manual Locking, Up and Down Brakes Hydraulic Front

RailKut

Engine Type	Tier 4 Final 4 Cyl., Turbo Diesel
Horsepower	74 HP @ 1,800 RPM
Throttle Control	Electronic Adjustable
Hydraulic System	45 GPM @ 3,250 PSI
Safety Stop	7 Second Shut Down
Truck Bed	Quick Removable

Standard Equipment

Rafna Rail Gear
Spare Tire and Rim
Torque Wrench with Rotary head
Directional Light Bar
Emergency Hyraul Retract

SAFETY FEATURES

Master ON/OFF Switch
Operator Presence Switches on Right Side Door
Mower Safety Start Switch
Brush Guard Extending Over Cab
Operator Protective Screen Covers Right Hand Door
Manual Emergency Over-ride

Accessories

Snow Panther
Saw Blade
Growler Mulcher
Fire Suppresion
Ditcher
Boom Sweeper



GROWLER MULCHER



SAW BLADE



SNOW PANTHER



OPTIONAL TRAILER HITCH



FIRE SUPPRESSION



DITCHER



BOOM SWEEPER

Boom Mower

	RK-22	RK-24		ROTARY	FLAIL
Cutter Reach Up	19' 10"	21' 2"	Cutting Width	50" / 60"	50" / 63"
Cutter Reach Out	21' 6"	23' 2"	Cutting Head Weight	785 lbs. (Minimum)	835 lbs. (Minimum)
Cutter Reach Down	12' 5"	13' 5"	Cutting Assembly	One-piece forged alloy spindle with stationary wire guards and a one-piece formed dishpan.	61" knife swing circumference 2,200 RPM cutter shaft
Controls	Electronic Joystick	Electronic Joystick			
Transport Width	8' 6"	8' 6"	Blade Options Full Swing	Two, Three, Four or Six	
Transport Stow Height	11' 8"	13' 5"	Brush	5/8" x 5" x 17.125"	24 cast, 33 oz. knives
			Grass (High Suction)	5/8" x 5" x 17.125"	48 all-purpose knives

Tiger Corporation
3301 N. Louise Ave.
Sioux Falls, SD 57107
800.843.6849
www.tigermowers.com

An Alamo Group® Company

Specifications are subject to change without notice.

Optional equipment may be shown. One Year Warranty on all products.



Dealer Info:

RBL, INC / ROBOLUBE
56 Plymouth Avenue North
Minneapolis, MN 55411
Phone: 612.339.9395
www.rblinc.com



MADE WITH PRIDE IN THE USA