

Tiger™ ROTARY AND FLAIL **RailKut**



Productivity. Performance. Power.

With the power and versatility of this innovative machine you can mow along rail, trim low branches or clear a highway intersection. Once job is done, you can drive the RailKut at highway speeds, improving overall productivity. Available in 22' and 24' boom lengths.



**On/off rail
applications**

DURABILITY INNOVATION
COMMITMENT



Features include right side viewing camera. Standard equipment on the RailKut.
Allows operator clear view of cutter head in operation while facing forward and steering vehicle.



Viewing Monitor located in cab of truck.



Specifications

Truck

F550 TRUCK		SAFETY FEATURES		Accessories	
Four Wheel Drive Truck		Master ON/OFF Switch		Snow Panther	
Engine	Turbo 8 cyl. Diesel	Operator Presence Switches on Right Side Door		Saw Blade	
Horsepower	325 HP @ 3,300 RPM	Mower Safety Start Switch		Growler Mulcher	
Fuel Tank	40 gallon, Supplies Both Engines	Brush Guard Extending Over Cab		Fire Suppression	
Steering	Dual Station, Power	Operator Protective Screen Covers Right Hand Door		Ditcher	
Hyrail System	Bolt On Rated to 28,000 lbs.	Manual Emergency Over-ride		Boom Sweeper	
	Manual Locking, Up and Down				
	Brakes Hydraulic Front				
RailKut					
Engine Type	Tier 4 Final 4 Cyl., Turbo Diesel				
Horsepower	74 HP @ 1,800 RPM				
Throttle Control	Electronic Adjustable				
Hydraulic System	45 GPM @ 3,250 PSI				
Safety Stop	7 Second Shut Down				
Truck Bed	Quick Removable				
Standard Equipment					
Rafna Rail Gear					
Spare Tire and Rim					
Torque Wrench with Rotary head					
Directional Light Bar					
Emergency Hyrail Retract					



GROWLER MULCHER



SAW BLADE



SNOW PANTHER



OPTIONAL TRAILER HITCH



FIRE SUPPRESSION



DITCHER



BOOM SWEEPER

Boom Mower

	RK-22	RK-24		ROTARY	FLAIL
Cutter Reach Up	19' 10"	21' 2"	Cutting Width	50"/ 60"	50"/ 63"
Cutter Reach Out	21' 6"	23' 2"	Cutting Head Weight	785 lbs. (Minimum)	835 lbs. (Minimum)
Cutter Reach Down	12' 5"	13' 5"	Cutting Assembly	One-piece forged alloy spindle with stationary wire guards and a one-piece formed dishpan.	61" knife swing circumference
Controls	Electronic Joystick	Electronic Joystick			2,200 RPM cutter shaft
Transport Width	8' 6"	8' 6"	Blade Options Full Swing	Two, Three, Four or Six	
Transport Stow Height	11' 8"	13' 5"	Brush Grass (High Suction)	5/8" x 5" x 17.125"	24 cast, 33 oz. knives
				5/8" x 5" x 17.125"	48 all-purpose knives

Tiger Mowers LLC
3301 N. Louise Ave.
Sioux Falls, SD 57107
800.843.6849
www.tigermowers.com

An Alamo Group® Company

Specifications are subject to change without notice.

Optional equipment may be shown. One Year Warranty on all products.



Dealer Info:
RBL, INC / ROBOLUBE
56 Plymouth Avenue North
Minneapolis, MN 55411
Phone: 612.339.9395
www.rblinc.com



MADE WITH PRIDE IN THE USA