



STANDARD & HEAVY DUTY

TrailKat

Mowers



TFR-HD 180



TK-120

DURABILITY INNOVATION

COMMITMENT



Pivot Hitch



Safety Cover



Cast Pan
Blade Carrier



TK-180



WetCut available
as option on all
models



Offset Hitch

Specifications

	TK-120	TK-180	STK-120	STK-180
Cutting Width	126"	180"	126"	180"
Overall Width	133"	187"	133"	187"
Overall Length	183"	183"	183"	183"
Transport Width, min	88"	96"	88"	96"
Deck Thickness	7GA (3/16")	7GA (3/16")	(1/4")	(1/4")
Weight (approx.)	4,800 lbs.	5,455 lbs.	5,100 lbs.	5,800 lbs.
Minimum PTO HP	60 HP	60 HP	70 HP	70 HP
Recommended PTO HP	75 HP	85 HP	70 HP	90 HP
Cutting Height	2" to 14"	2" to 14"	2" to 14"	2" to 14"
Ground Clearance	13.5"	13.5"	13.5"	13.5"
Cutting Capacity	4.5" Material	4.5" Material	5" Material	5" Material
Blade Overlap	6.0"	6.0"	6.0"	6.0"
Divider Gear Box Rating	250 HP	250 HP	325 HP	325 HP
Center/Wing Gearbox Rating	225 HP	225 HP	285 HP	285 HP
Blade Tip Speed	540 PTO RPM	540 PTO RPM	540 PTO RPM	540 PTO RPM
Center	16,286 ft/min	16,286 ft/min	13,436 ft/min	13,436 ft/min
Wing	16,422 ft/min	16,422 ft/min	13,169 ft/min	13,169 ft/min
Wing Working Range	25° down to 90° up	25° down to 90° up	25° down to 90° up	25° down to 90° up
Walking Axle Center	Optional	Optional	Standard	Standard
Walking Axles Wings	Available option	Available option	Available option	Available option
LED Light Kit	Standard	Standard	Standard	Standard
Required Tractor Remotes	2 Remotes	3 Remotes	2 Remotes	3 Remotes

Specifications

Tiger's Offset Hitch (TOH)

Allows the tractor to remain on the road while the mower is fully in the ditch.
Provides operator safety and comfort with the ability to mow steep ditches without leaving the road.
Attaches to 10" and 15" Trailkat mowers.

Tiger's Offset Hitch can be used with 540 or 1000 PTO

Swivel mounted gear boxes designed to keep drive shafts in line at all times.

Patented strut arm allows backing up like 2 wheel trailer.

Low center of gravity design provides visibility to cutter head.

Transport width is 102"

Machine weight 2,757 lbs.

Offset Hitch extends mower to the right rear of tractor.

Drive line rated at 136 hp.

Gear boxes rated at 200 hp continuous.

LED lights included.




The Tiger Trailkat pull behind mowers in 5', 6' and 7' sizes are designed to add flexibility, productivity and value to your tractor.

Built strong to handle your toughest mowing terrain with ease.

Fast and easy hook up with Tiger's 3 point hitch design, this mower can make quick work of your mowing and can disconnect when finished so tractor can be used for other work.

SPECIFICATIONS

	TK-5	TK-6	TK-7
Cutting Width	60"	72"	84"
Overall Width	66"	78"	88.5"
Overall Length	88"	100"	130"
Deck Thickness	10Ga	10 Ga	10Ga
Weight (approx.)	988 lbs.	1,158 lbs.	1,350lbs.
Hitch	CAT I & QH	CAT I & QH	CAT I & QH
Gearbox Rating	130 HP	130 HP	130 HP
Recommended PTO HP	35 HP	45 HP	60 HP (Lift) 45 HP (Pull)
Cutting Height (Min)	1 1/2"	1 1/2"	1 1/2"
Cutting Capacity (Max)	2"	2"	2"
Side Skirt	10 Ga. x 9 1/4"	10 Ga. x 9 1/4"	10 Ga. x 9 1/4"
Slip Clutch	Standard	Standard	Standard
Blade Tip Speed	13,572 ft/min	16,286 ft/min	16,328 ft/min



Dealer Info:

Tiger Mowers LLC
 3301 N. Louise Ave
 Sioux Falls, SD 57107
 800-843-6849
www.tigermowers.com
 An Alamo Group Company



MADE WITH PRIDE IN THE USA

Specifications are subject to change without notice. Optional equipment may be shown. One Year Warranty on all products.