



Extreme Duty Triple Flail Mowers



This Tiger Triple Flail Mowing system was created to help you cover more ground efficiently, in less time, with excellent cut quality!

With a cut path of over 21 feet, this mowing solution increases your productivity, provides the ability to operate three heads independently and provides excellent visibility in the field. The Tiger Triple Flail Mower is the right choice to mow large areas of ground leaving a groomed appearance and clean cut.

Designed and built for the John Deere 6105E tractor.

Looking to maximize your mowing potential, look to the Tiger Triple Flail Mowers for unrivaled power to get the job done.



DURABILITY INNOVATION

COMMITMENT

Tiger Features

Productive. Efficient. Cover large areas fast..

Included on the Tiger Triple Flail Mowers are new draft beams with outstanding ground clearance. This makes driving over obstacles such as high curbs or operating the mower in undulating ground a breeze.

Now integrated into base equipment for the triple flail is an egress system that allows the operator entry into the tractor cab by lowering the left hand mower deck safely from outside of the tractor. The controls for this system are located at the front of the tractor near the hydraulic tank.



**NEW DRAFT BEAMS
WITH HIGHER GROUND CLERENCE**



EGRESS SYSTEM



**8" GROUND ROLLERS
WITH ADJUSTABLE
CUTTING HEIGHT**



TRAVEL POSITION

This mowing solution was engineered and designed for airports, interstates, landfills, college campuses or anywhere there is a need for wide area mowing. With a cut path of over 21 feet, this high performance mower is built to save your municipality time and money. The Tiger Triple Flail Mowers offer productivity, higher visibility and maneuverability to avoid obstacles in your way, making this a must have product. Contact your local Tiger Dealer for more information on this amazing mower.

Features

Cut Width

Over 21 Ft.- (75" sides -110" rear), Over 23 Ft - (90 sides)

Travel Width

Approx 11' in stowed transport position

High Berm Lift System

Designed to go over high berms and curbs

Egress System

Control of left side flail from outside of cab-standard

Safety Stop

7 Second Shut Down

Cutter Heads

75" or 90" sides - 110" rear Flail

Cutting Height

1 1/2" to 7 1/2"

Cutter Shaft

6" diameter

Ground Roller

8" diameter, for uniform cutting and longer bearing life

Cutter Knife

Self cleaning, forged and reversible knives

Cutter Housing

7 gauge steel with 1/2" carrier side steel plates

Skid Shoes

Replaceable

Tiger Corporation
3301 North Louise Ave.
Sioux Falls, SD, USA 57107
800.843.6849
www.tigermowers.com



Dealer Info:

An Alamo Group® Company
Specifications are subject to change. Optional equipment may be shown.

Meets All Applicable ANSI / SAE Test Standards.
© 2019 Tiger Corporation. All Rights Reserved. Printed in the USA.

