



# Extreme Duty Triple Flail Mowers



This Tiger Triple Flail Mowing system was created to help you cover more ground efficiently, in less time, with excellent cut quality!

With a cut path option of over 23 feet, this mowing solution increases your productivity, provides the ability to operate three heads independently and provides excellent visibility in the field. The Tiger Triple Flail Mower is the right choice to mow large areas of ground leaving a groomed appearance and clean cut.

Designed and built for the John Deere 6105E tractor.

Looking to maximize your mowing potential, look to the Tiger Triple Flail Mowers for unrivaled power to get the job done.



DURABILITY    INNOVATION  
COMMITMENT



# Tiger Features

## Productive. Efficient. Cover large areas fast..

Included on the Tiger Triple Flail Mowers are new draft beams with outstanding ground clearance. This makes driving over obstacles such as high curbs or operating the mower in undulating ground a breeze.

Now integrated into base equipment for the triple flail is an egress system that allows the operator entry into the tractor cab by lowering the left hand mower deck safely from outside of the tractor. The controls for this system are located at the front of the tractor near the hydraulic tank.



**NEW DRAFT BEAMS  
WITH HIGHER GROUND CLERENCE**



**EGRESS SYSTEM**



**8" GROUND ROLLERS  
WITH ADJUSTABLE  
CUTTING HEIGHT**



**TRAVEL POSITION**

This mowing solution was engineered and designed for airports, interstates, landfills, college campuses or anywhere there is a need for wide area mowing. With a cut path option of over 23 feet, this high performance mower is built to save your municipality time and money. The Tiger Triple Flail Mowers offer productivity, higher visibility and maneuverability to avoid obstacles in your way, making this a must have product. Contact your local Tiger Dealer for more information on this amazing mower.

### Features

<b>Cut Width</b>	Over 21 Ft.- (75" sides -110" rear), Over 23 Ft - (90 sides)
<b>Travel Width</b>	Approx 11' in stowed transport position
<b>High Berm Lift System</b>	Designed to go over high berms and curbs
<b>Egress System</b>	Control of left side flail from outside of cab-standard
<b>Safety Stop</b>	7 Second Shut Down
<b>Cutter Heads</b>	75" or 90" sides - 110" rear Flail
<b>Cutting Height</b>	1 1/2" to 7 1/2"
<b>Cutter Shaft</b>	6" diameter
<b>Ground Roller</b>	8" diameter, for uniform cutting and longer bearing life
<b>Cutter Knife</b>	Self cleaning, forged and reversible knives
<b>Cutter Housing</b>	7 gauge steel with 1/2" carrier side steel plates
<b>Skid Shoes</b>	Replaceable

Tiger Mowers LLC  
3301 North Louise Ave.  
Sioux Falls, SD, USA 57107  
800.843.6849  
www.tigermowers.com



### Dealer Info:

An Alamo Group® Company  
Specifications are subject to change. Optional equipment may be shown.

Meets All Applicable ANSI / SAE Test Standards.  
© 2022 Tiger Corporation. All Rights Reserved. Printed in the USA.

